

# SWITCH DISCONNECTOR



40A 2P IP66/IP69 110x150x87mm Y1 EMERGENCY YELLOW/RED

COD. 590.EM4012.S

## Notes

- Handle padlockable in OFF only (3 padlocks)
- Equipped with door interlock
- Break-through cable entries
- Supplied with 2 M25 cable glands for cables Ø13-18mm

## TECHDATA

Synthetical description	SWITCH DISCONNECTOR
Material	ENGINEERING PLASTIC
Protection degree IP	IP66/IP69
Type	EMERGENCY
Colour	YELLOW/RED
Rated current	40A
Poles	2P
Switch size	Y1
Dimensions	110x150x87mm

## STANDARDS AND LAWS

EN 60947-3 (2006)

[European Standard] Low-voltage switchgear and controlgear - Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units

EN 60947-1 (2007)

[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules

EN 60947-1/A1 (2011)

[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules

EN 60947-3/A1 (2011)

[European Standard] Low-voltage switchgear and controlgear Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units

EN 60947-1/A2 (2014)

[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules

EN 60947-3/A2 (2015)

[European Standard] Low-voltage switchgear and controlgear Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units

DIRECTIVE LOW VOLTAGE 2014/35/EU

[European Directives] Low Voltage Directive